

PRD N° 0230 B

Membro degli Accordi di Mutuo
Riconoscimento EA, IAF e ILAC
Signatory of EA, IAF and ILAC
Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2020/12/10 n. **875205001/OE** Validity: 2025/07/07

This Certificate cancels & replaces the previous one n° 875202805/OE dated 2020/07/08.

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

Manufacturer: (Responsible of the PPE)	Red Wing Shoe Company, Inc. 314 Main Street, Red Wing, MN 55066 – USA
Type of PPE:	Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials)
Category of PPE:	II: "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force.

Mod<mark>el "3251"</mark>

Description: <u>model</u>: A (low shoes);

fastening system: by means of laces;

processing: RIM (reaction injection mould);

<u>outsole</u>: black 99666 PU MUNRO Classic Red Wing bicolor A3 declared not antistatic (61GH0001.331);

<u>upper</u>: brown 4400 leather declared "mezza bovina pelle fiore art. "Puma macchiato" hydro spessore dichiarato 1,8/2,0 mm colore passante" (10BF1932.400);

<u>collar</u>: black leather declared "vitelli fiore per fodera art. "California hydro" spessore dichiarato 1,0/1,2 mm colore passante" (10BF1940.300);

tongue/bellows: same leather as that of the upper declared thickness 1,0/1,2 mm lined with the quarter lining and padded;

<u>vamp lining</u>: Maleo gray 63569 non-woven fabric article TETRA declared mass per unit area 300 gr/mq (24TF0630.100);

<u>auarter lining</u>: black knitting article AERPLUSS BS declared mass per unit area 210 gr/mq (24TT3710.300):

heel-grip: black microfiber article MICROSUEDE 0,8 (21ST2930.300);

insole: multi-layered fabric article Q-FLEX TX T6 "R" ISOLANTE green print (27ST0979.131)

which also serves as penetration resistant insert;

removable insock: thermoformed, red soft PU with Red Wing logo (27SP1370.500);

toecap: made of glass fiber article F16 CONTENDER (37LA0056.330).

Technical Standard:

EN ISO 20344:2011
Personal protective equipment – Test methods for footwear

(UNI EN ISO 20345:2011
Personal protective equipment – Safety footwear

(UNI EN ISO 20345:2012)

Intended use: general industry, engineering industry, agriculture, warehouses, works on trucks, cranes.

Size range: from 35 to 48

Technical File: DC-12125/E

Test report: RCT n°3912113.01/E



DBD No 0530 B

Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2020/12/10 n. **875205001/OE** Validity: 2025/07/07

Functions and performance levels:

basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which:

SRC = Slip resistance – meets the following requirement:

- <u>surface</u>: ceramic / <u>lubricant</u>: detergent solution;
- surface: steel / lubricant: glycerol.

Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011):

E = energy absorption of seat region; **FO =** resistance to fuel oil of the outsole; **WRU =** resistance to water penetration and absorption; **P =** penetration resistance of the sole.

Note: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption).

Marking:

on a stitched label and displaying the following information:

- CE Marking;
- Name/Logo and complete address of the Manufacturer;
- designation of the footwear (article code: unique/unambiguous);
- nr. and year of the Standard of reference + safety symbols;
- size of the footwear (EU + USA + EUK);
- production date (month + year);
- additional information: internal codes, batch number.

Additional marking in accordance with the ASTM F2413-18 standard (not covered by this certification).



ASTM F2413-18 M/I/C EH PR



NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements.

The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).

