

PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/12/22

n. 875215105/OE

Validity: 2026/12/21

The hereunder described items of Personal Protective Equipment have overcome positively the "EU type examination" (Module B), proving their conformity to the safety and health requirements of the Regulation (EU) 2016/425 (Annex II)

| Manufacturer: (Responsible of the PPE) | Red Wing Shoe Company, Inc. 314 Main Street, Red Wing, MN 55066 – USA |
|--|---|
| Type of PPE: | Safety footwear in conformity with EN ISO 20345:2011 class I (= footwear in leather and other materials) |
| Category of PPE: | II : "medium" risks. This certificate is based on reference standards listed below: its validity is no longer ensured should new version of the standards come into force. |
| Model | "3296" |
| Description: | <u>model</u> : A (low shoe); <u>fastening system</u> : by means of boa-system; <u>processing</u> : direct injection RIM (reaction injection mould); <u>outsole</u> : orange PU "MUNRO TRAINER RED WING" marked MADE IN ITALY OIL/SLIP RESISTANT declared ESD (61GH0002.255); <u>midsole</u> : polverone 64144 foam PU; <u>upper</u> : black/grey fabric PERSPAIR MT064 matched with microfiber (5TC34480.300), and insert in the heel area of grey leather SCAMOSCIATO RETINATO HYDRO declared thickness 1,8-2,0 mm (13B51026.201); <u>collar</u> : black fabric nylon "RIB + TELA LEGGERA + RETICOLO + TELA 1300" (24TT6010.300); <u>tongue/bellows</u> : black fabric TECNIC L 1081 + CALIF. 5005 IDRO color black (21SX0544.PB4), reinforced with the same leather of the upper, centrally lined and padded; <u>vamp lining</u> : Maleo gray 63569 non-woven fabric TETRA declared gr/mq 300 (24TF0630.100); <u>quarter lining</u> : orange three-dimensional fabric ASTERIX (24TT3710.505); <u>heel-grip</u> : black microfiber MICROSUEDE 0,8 (21ST2930.300) insole: multi-layered fabric, article Q-FLEX TX T6 MXC "R" red print "CONDUTIVO ESD" (27ST0977.131), which also serves as penetration resistant insert; <u>removable insock</u> : thermoformed, article 1 451 431, red soft PU match with black fabric J-MICRO perforated with Red Wing logo + ESD SOFT PU HEEL SUPPORT (27SP1278.330); <u>toecap</u> : made of glass fiber, article F16 CONTENDER (37LA0056.330). |
| Technical Standard: | EN ISO 20344:2011 (UNI EN ISO 20344:2012)Personal protective equipment – Test methods for footwearEN ISO 20345:2011 (UNI EN ISO 20345:2012)Personal protective equipment – Safety footwear |
| Intended use: | general industry, engineering industry, agriculture, warehouses, works on trucks, cranes. |
| Size range: | from 35 to 48 |
| Technical File: | DC-13839 |





PRD N° 0230 B Membro degli Accordi di Mutuo Riconoscimento EA, IAF e ILAC Signatory of EA, IAF and ILAC Mutual Recognition Agreements





EU Type Examination Certificate

Date: 2021/12/22

n. 875215105/OE

Validity: 2026/12/21

| Test report: | RCT n°4014205.01/E |
|--|---|
| Functions and performance levels: | basic requirements for safety footwear (SB) (see Table 2 and 3 of EN ISO 20345:2011): all mandatory ones, among which: |
| | SRC = Slip resistance – meets the following requirement: - <u>surface</u> : ceramic / <u>lubricant</u> : detergent solution; - <u>surface</u> : steel / <u>lubricant</u> : glycerol. |
| | Additional requirements (Tab. 18 and 20 of EN ISO 20345:2011): S3 = closed seat region, antistatic properties, energy absorption of seat region, resistance to fuel oil, water penetration resistance and absorption (water-repellent upper), penetration resistance, cleated outsole. |
| | Note 1: the penetration resistance of the synthetic stitch proof insole tends to decrease with the diameter of the perforating object; in return the synthetic insole offers more protective surface and ergonomics advantages (flexibility, insulation, humidity and impact absorption). Note 2: the footwear also meets the requirement in accordance with IEC 61340-5-1:2016 (IEC 61340-4-3:2017) for the electrical resistance ESD (electric dissipative footwear). |
| Marking: | on a stitched label and displaying the following information: - CE Marking ; - Name/Logo and complete address of the Manufacturer; - designation of the footwear (article code: unique/unambiguous); - nr. and year of the Standard of reference + safety symbols; - size of the footwear (EU + USA + EUK); - production date (month + year); - additional information: internal codes, batch number. |
| RED WI | ING S° |
| 314 Main Street, Red W EN ISO 203 S3 SI 3296 | 345:2011 |
| EU USA 38 8 4916 02/ | EUK CM 8 24.5 |

NOTE: the Technical File contains a more detailed description of the PPE (material, method of assembly, photographs or drawings), performance data, safety functions and level of protection, elements of conformity to the basic and supplementary requirements. The Technical File is integral part of the present Certification, which has to be kept available by the applicant to be forwarded - upon request - to the entitled person (supervising body, Controlling Officer).



Certificato ue E rev05 - 26/10/20